



CODE 0.541

spazio

Professional water-repellent breathable latex paint for interiors

GENERAL PROPERTIES

SPAZIO is a breathable wall paint which offers an optimal whiteness, remarkable brushing and spreading. It is ideal for prestigious finishes on indoor walls.

The exceptionally high level of breathability makes SPAZIO particularly suitable for painting interiors subject to condensation (kitchens, bathrooms etc.).

INSTRUCTIONS

Substrate preparation:

- Bare interior surfaces: clean thoroughly and remove any unsound plaster using a broomcorn brush. Level any imperfections (holes, cracks or crazing) with LITOSTUCCO applying as many times as necessary. Allow 6 hrs, sand the stuccoed areas and clean thoroughly.
- The choice of sealer depends on the conditions of the substrate. ISOLEX W or ARDFIX are suitable in most cases. Use BIANCOFIX (fixative hiding sealer) on particularly dark surfaces. Allow to dry and apply SPAZIO.
- Interior walls with sound distemper paintwork: clean thoroughly and stucco any imperfections with LITOSTUCCO (as indicated above). After sanding, seal the stuccoed areas with ARDFIX. If the substrate is unsound or chalky treat the whole surface with ISOLEX W or ARDFIX. Allow 6 hrs before applying SPAZIO.
- Interior walls with washable latex paintwork: clean thoroughly, stucco any imperfections, sand and dust. Seal the stuccoed areas with a hand of ARDFIX. Allow 4 hours & apply SPAZIO.

Application:

Apply SPAZIO as follows:

- Brush: stir well, thinning at 50-60% in water volume and apply by cross-brushing. Allow 1-2 hrs before applying the second hand.
- Roller: thin at 40-50% in water volume.
- Airless-spray gun: use a 0.25 mm Ø nozzle to thin at approx. 40-50% in water volume.

- SPAZIO is easy to tint with the universal colorants COLORATUTTO.
- Store in cool, frost free premises.
- Wash equipment immediately after use with water.
- Do not apply at ambient/substrate temperature below +5°C or above +35°C.
- SPAZIO is compatible with the 16COLOURS & WIZARD tinting systems.
- Use in compliance with the current Health & Safety Regulations. Do not release the containers into the environment.
- Refer to the PSDS for further details.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1720 ± 50g/l	
VISCOSITY AT 20°C	16.000 ± 2000 cP	
COLOUR	White	
DRYING	TOUCH DRY	1,5 hrs
	THROUGH DRYING	24 hrs
CONTRAST RATION	EN 13300 (ISO 6504-3)	Class 2 to 5 m²/l
GLOSS (85°)	EN 13300 (EN ISO 2813)	< 5 G.U. Dead Matt

YIELD

2 layers imply a yield of 5 - 5,5 m²/l. Said yield refers to smooth surfaces with medium absorption. We recommend testing on the specific surface.

TENDER SPECIFICATION ITEM

BREATHABLE HIGH COVERING LATEX PAINT FOR INTERIORS

Two coat application on treated surfaces of breathable high covering latex paint for interiors based on synthetic copolymers in aqueous dispersion & hiding pigments -SPAZIO - with a minimum consumption of 0,2 l/m².

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2024/02



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: assistenza@ard-raccanello.it