



CODE 0.524.1010

unique

washable latex paint for interiors with an high covering power

GENERAL FEATURES

UNIQUE is a washable odourless latex paint with an high covering power, featured by a good water vapour permeability. It offers matt and consistent finishes, even with one layer. UNIQUE is an extremely versatile product, devised for painting two coat plaster work and for direct application on plasterboard.

Without formaldehyde, in A+ class thanks to the lowest emissions of volatile substances, UNIQUE guarantees healthy environments from the time of application to its complete maturation, and therefore protecting the environment and the human health. Compliant with CAM standards (minimum environmental criteria) section 2.5.1, section 2.5.13 requirement b), section 3.2.8, according to D.M. June 23rd 2022 and following GURI publication on 6th August 2022.

INSTRUCTIONS

Substrate preparation

- Bare interior walls: brush thoroughly removing all dust, dirt & unsound plaster. Level imperfections, craking holes and craks with LITOSTUCCO making continuous shavings; allow 24 hours, check the wall is perfectly dry. Plasterboard does not require sealer and can be directly finish with UNIQUE.
With particularly chalky surfaces, apply one layer of ISOLEX W or of ARDFIX previously diluted. Allow at least 4 hours and apply one layer of UNIQUE.
If needed, allow at least 3 hours, apply a second layer of UNIQUE.
- Interior walls already painted with washable latex paints: clean thoroughly, stuccoing eventual imperfections, sand & remove dust, seal the stuccoed areas with a layer of ISOLEX W or of ARDFIX properly diluted with water; allow at least 4 hours proceed with the application of UNIQUE.
If needed, allow at least 3 hours and apply a second layer of UNIQUE.

Application

UNIQUE can be applied with the following tools and options:

- Roller: properly mix the product, dilute with the 10-15% in water volume.
- Brush: properly mix the product, dilute with the 15-25% in water volume.
- Airless Spray gun: dilute about with the 20-25% in water volume using a Ø 0,25 mm nozzle.
- Store the product in cool, frost free premises. Wash equipment immediately after use with water.

- Do not apply at ambient or substrate temperature below +5°C or above +35°C.
- Use in compliance with the current Health & Safety Regulations; after using do not waste the containers into the environment. Refer to the MSDS for further information.

TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1520 ± 50 g/l	
VISCOSITY AT 20°C	5.500 ± 1000 cP	
COLOUR	White	
DRYING AT 20° C	TOUCH DRYING	2 h
	THROUGH DRYING	24 h
WATER VAPOUR PERMEABILITY	EN 7783-1 E 2	Class V₁ (high)
FRENCH DECREE 321/2011	Class A+	
WET SCRUB RESISTANCE	EN 13300 (ISO 11998)	Class 3
CONTRAST RATION	EN 13300 (ISO 6504-3)	Class 1 to 6 m²/l
GLOSS (85°)	EN 13300 (EN ISO 2813)	< 5 G.U. Dead Matt

YIELD

A one ply cycle implies a yield of about 10-12 m²/l. This yield refers to smooth surfaces with medium absorption; however, it is best to determine the same by testing.

TENDER SPECIFICATION ITEM

WASHABLE LATEX PAINT WITH HIGH COVERING POWER, FOR CONSISTENT FINISHES EVEN WITH ONE LAYER.
A one or two layer application on prepared surfaces of washable odourless matt latex paint with high covering power as UNIQUE with a minimum consumption of 0,085 l/m².
€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2024/02



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: assistenza@ard-raccanello.it