



CODE 0.079

## **biancofix**

Fixative hiding sealer

---

### **GENERAL PROPERTIES**

BIANCOFIX is an impregnating pigmented primer suitable as an undercoat, for emulsion paints and plastic coatings. Apart from the common properties found in impregnating agents (substrate penetration, sealing effect, alkalinity barrier on concrete) the hiding power of this product is such that one of the finishing coats can be saved.

BIANCOFIX can be applied on any mineral support. Its use is particularly advantageous on smooth & compact surfaces (such as plaster & plasterboard); on walls with traces of puttying & patching, on surfaces with radiator smudges or which have been painted with dark colours. Furthermore, it may also be used as a primer for surfaces to be treated with plastic coatings.

### **INSTRUCTIONS**

#### **Substrate preparation:**

**Exterior walls:** according to the type of substrate, clean by sandblasting, high pressure water washing, mechanical or manual brushing. Mould, moss & bacteria must be cleaned accurately & treated with ARDSAN RISANANTE MURALE. Ensure the substrate is perfectly dry and apply BIANCOFIX. Consolidate chalky surfaces with a coat of ISOLEX W or ISOLEX.

**Interior walls:** clean thoroughly, stucco any imperfections with LITOSTUCCO. After 6 hrs sand, clean thoroughly and apply a coat of BIANCOFIX.

Chalky or unsound distemper painted surfaces: it is advisable to apply a consolidating impregnating agent such as ISOLEX W or ARDFIX .

#### **Application:**

- The product is ready for use. Stir well and apply one coat by brush, distributing the product uniformly.
- In the case of extremely absorbent surfaces or high temperatures dilute up to a max of 10%. Allow at least 4 hrs & proceed with the finishing products.
- Wash equipment with water, immediately after use.

- Do not apply if the ambient or substrate temperature is below + 5 C° or above + 35 C°. Avoid applying under direct sunlight.
- Store in a cool place; protect against from frost.
- BIANCOFIX can be easily tinted with the universal colorants COLORTUTTO 0.951.
- Use in compliance with current Health & Safety Regulations. Dispose of spent material/containers according to the same.

Refer to the PSDS for further details.

## TECHNICAL PROPERTIES

SPECIFIC WEIGHT	1440 ± 50 g/l
VISCOSITY AT 20°C	2600 ÷ 3200 cps
NATURE OF BINDER	Styrene – acrylic copolymers

## YIELD

The correct application on walls with medium absorption implies a coverage of 7-10 m<sup>2</sup>/l.

## TENDER SPECIFICATIONS

### FIXATIVE HIDING SEALER

Brush application on pretreated wall surfaces of hiding impregnating sealing agent based on styrene-acrylic copolymers in aqueous dispersion and mineral extenders type BIANCOFIX with an approximate consumption of 0,10 - 0,14 l/m<sup>2</sup>.

€/ m<sup>2</sup>.

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide.  
Revision 2015/06



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1ª Strada, 13 – Tel. 049.8060000 (5 linee)  
Fax 049.773749 – [www.ard-raccanello.it](http://www.ard-raccanello.it) - E-mail: [assistenza@ard-raccanello.it](mailto:assistenza@ard-raccanello.it)