



CODE 0.074.

primer murale

Mineral based neutralizer for interior & exterior walls

GENERAL PROPERTIES

PRIMER MURALE is a particular product based on mineral salts & specific additives in a concentrated aqueous solution. Its versatile performance lends an optimal solution for the most common problems such as:

Patching: PRIMER MURALE is ideal for retreating surfaces with patches of smoke, nicotine, soot, damp (due to old water infiltrations).

Sealing: optimal combination of penetration & impregnation reducing the surfaces' absorption.

Consolidation: the crystallization of the salts in the plaster's capillary network arrests the chalking & decaying process of mineral surfaces.

PRIMER MURALE is suitable for interior & exterior surfaces in cement/lime plaster, plaster of Paris, plasterboard & old sound paintwork.

INSTRUCTIONS

Substrate preparation:

- Bare walls: ensure the wall has weathered for at least 28 days. Clean thoroughly, removing dust, filth & any unsound parts.

Application:

Apply PRIMER MURALE as follows:

- PRIMER MURALE can be applied neat using a brush or spray. We recommend thinning at 100% in water volume when treating surfaces with poor absorption.
- When neutralizing patches, the impregnation of the margins of the compressed areas require particular attention.
- During application protect any metal parts, marble & glass,
- After application exterior surfaces must be protected against rain for at least 24 hrs.
- When applying on painted surfaces any excess will deposit a powder which must be removed before recoating.
- Caution: the product reacts with normal powder/paste stuccoes causing blisters and flaking. Apply a localized hand of latex paint between the PRIMER MURALE & the stucco to avoid this problem.
- Do not apply at ambient/substrate temperatures below +5°C or above +30°C.

- Use in compliance with current Health & Safety Regulations. Dispose of spent material/containers according to the same.

TECHNICAL PROPERTIES	SPECIFIC WEIGHT	1200 ± 30g/l
	NATURE OF BINDER	mineral
	THINNER	water
	DILUTION % BY VOLUME	0 – 100%
		neat
	RECOATABLE	24 hrs

YIELD The yield varies according to the absorption of the substrate; 8-10 m²/l is an approx guide.

TENDER SPECIFICATION ITEM MINERAL BASED NEUTRALIZER FOR INTERIORS & EXTERIORS

Brush/spray application on treated surfaces of an int/ext neutralizer based on mineral salts & specific additives which seal, consolidate & neutralize the substrate preserving the mineral characteristics of the surface type PRIMER MURALE with a minimum consumption of 0,10 l/m².

€/m²

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2016/12



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: assistenza@ard-raccanello.it